1309.0312 [Repealed, 32 SR 12]

1309.0312 SECTION R312, GUARDS AND WINDOW FALL PROTECTION.

Subpart 1. **IRC section R312.1.1, Where required.** Section R312.1.1 is amended as follows:

R312.1.1 Where required. Guards shall be located along the open sides of floors, stairs, ramps, and landings that are located more than 30 inches (762 mm) measured vertically to the floor or grade below. Insect screening shall not be considered as a guard.

Subp. 2. IRC section R312.2, Window fall protection. Section R312.2 is amended to read as follows.

R312.2 Window fall protection. Window fall protection shall be provided in accordance with sections R312.2.1 and R312.2.2.

R312.2.1 Window sills. In dwelling units, where the lowest part of the opening of an operable window is located more than 72 inches (1829 mm) above the finished grade or surface below, the lowest part of the window opening shall be a minimum of 36 inches (914 mm) above the finished floor of the room in which the window is located. Operable sections of windows shall not permit openings that allow passage of a 4-inch diameter (102 mm) sphere where such openings are located within 36 inches (914 mm) of the finished floor.

Exceptions:

1. Windows with openings that will not allow a 4-inch diameter (102 mm) sphere to pass through the opening when the window is in its largest opened position.

2. Openings that are provided with window fall prevention devices that comply with ASTM F 2090.

3. Windows that are provided with window opening control devices that comply with section R312.2.2.

4. Replacement windows.

R312.2.2 Window opening control devices. Window opening control devices shall comply with ASTM F 2090. The window opening control device, after operation to release the control device allowing the window to fully open, shall not reduce the minimum net clear opening area of the window unit to less than the area required by section R310.1.1.

Statutory Authority: MS s 326B.02; 326B.101; 326B.106

History: 39 SR 91

Published Electronically: January 26, 2015