

**7011.2105 SPRAYING OF INORGANIC FIBROUS MATERIALS.**

The spraying on any portion of a building or structure open to the outdoor atmosphere of any acoustical insulating, thermal insulating, or fireproofing product which does not contain asbestos but which contains inorganic fibrous material shall occur only under the following procedures:

A. The entire floor area where the spraying is to occur shall be enclosed with plastic-coated tarpaulins or by other means in a manner which shall prevent the escape of sprayed material from the enclosure. All interior areas, such as elevator shafts and stairwells, shall be enclosed in a manner which shall prevent the escape of sprayed material from the working area.

B. The entire area in which spraying has occurred, including all ledges, surfaces, equipment, and protective tarpaulins within the enclosure, shall be thoroughly cleaned by means of scraping, sweeping, vacuuming, or other acceptable methods upon completion of the spraying operation and before the enclosure is dismantled; provided, however, that all such cleaning procedures shall be followed by thorough vacuuming. The collected material shall be placed in a sealed container or bag strong enough to resist breaking and tearing under normal handling conditions and shall be transported directly to a disposal site approved by the commissioner.

C. All areas for opening containers of the material to be sprayed and for loading the material to be sprayed into hoppers, or other containers shall be enclosed in a manner which shall prevent the escape of the material to be sprayed to the outdoor atmosphere.

**Statutory Authority:** *MS s 116.07*

**History:** *L 1987 c 186 s 15; 18 SR 614*

**Published Electronically:** *February 25, 2008*