7083.4020 TEST **RESULTS** REPORTING REQUIREMENTS **FOR** PROPRIETARY TREATMENT PRODUCTS.

TABLE II

Treatment component/sequence category

Category A: Designed to treat sewage with strength typical of a residential source when septic tank effluent is anticipated to be equal to or less than treatment level C (Table III, part 7083.4030)

Testing results reported

Report test results for influent and effluent sampling obtained throughout the testing period for evaluation of consistent reduction for the parameters CBOD₅ and TSS:

- Average
- Minimum
- Median
- 30-day average (each month)
- Standard deviation
- Maximum
- Interquartile range.

For bacteriological reduction performance, report fecal coliform test results of influent and effluent sampling by geometric mean from samples drawn within 30-day or monthly calendar periods, obtained from a minimum of three samples per week throughout the testing period. See part 7083.4060. Test report must also include the individual results of all samples drawn throughout the test period.

Category B: Designed to treat high-strength sewage when septic tank effluent is anticipated full test average values of influent and to be greater than treatment level C (Table III, part 7083.4030), including restaurants, grocery stores, mini-marts, group homes, medical clinics, residences, etc.

Report all individual test results and effluent sampling obtained throughout the testing period for CBOD₅, TSS, and oil and grease. Report the treatment capacity of the product tested in pounds per day for CBOD₅.

Total nitrogen and phosphorus reduction in Categories A and B

Report test results on all required performance criteria according to the format prescribed in the test protocol described in Table I, part 7083.4010.

Statutory Authority: *MS s 115.03; 115.55*

History: 32 SR 1420

Published Electronically: August 29, 2013