```
08/21/89
```

31

Department of Public Safety 1 2 3 Adopted Permanent Rules Relating to the Uniform Fire Code 4 Rules as Adopted 5 7510.3100 PURPOSE. 6 7 The purpose of parts 7510.3100 to 7510.3270 7510.3280 is to adopt uniform fire safety standards governing the maintenance of 8 9 buildings and premises; regulate the storage, use, and handling of dangerous and hazardous materials, substances, and processes; 10 11 and regulate the maintenance of adequate egress facilities. 7510.3110 SCOPE. 12 13 The scope of parts 7510.3100 to 7510.3270 7510.3280 is intended to be consistent with Minnesota Statutes, section 14 299F.011. 15 7510.3120 RULES AND STANDARDS ADOPTED BY REFERENCE. 16 The Uniform Fire Code, as promulgated by the International 17 Conference of Building Officials, and the Western Fire Chiefs 18 19 Association (Whittier, California, 1988) is incorporated by reference and made a part of Minnesota Rules pursuant to 20 21 statutory authority, subject to the alterations and amendments in parts 7510.3100 to 7510.3270 7510.3280. The Uniform Fire 22 Code is not subject to frequent change and is available at the 23 State Law Library, 117 University Avenue, Saint Paul, Minnesota 24 55155. 25 UNIFORM FIRE CODE AMENDMENTS 26 7510.3130 ARTICLE 1 OF UNIFORM FIRE CODE. 27 28 Sec. 1.101 of the Uniform Fire Code is amended to read: 29 Sec. 1.101. This code shall be known as the Minnesota Uniform Fire Code, may be cited as such, and will be 30 referred to herein as "this code." 7510.3140 ARTICLE 2 OF UNIFORM FIRE CODE. 32 Subpart 1. Sec. 2.102. Sec. 2.102 of the Uniform Fire 33 Approved 1

by Revisor

08/21/89

1 Code is amended to read:

2 Sec. 2.102. (a) Local Government Amendments to Article 2. Any jurisdiction which adopts this code is authorized to make 3 amendments, by ordinance or regulation, to Article 2 hereof to 4 provide for a system of enforcement and administration within 5 the jurisdiction. These amendments shall be equal to, in 6 addition to, or more stringent than this code. None of the 7 8 existing provisions of Article 2 shall be changed nor shall any amendment be made which interferes with the intent of the 9 10 existing provisions nor the state fire marshal's duties and 11 powers thereunder.

12 (b) Local Government Rules. Any jurisdiction which adopts 13 this code is authorized to adopt, by ordinance or regulation, rules for the prevention and control of fires and fire hazards 14 15 as may be necessary from time to time, to carry out the intent 16 of this code, and which may be more restrictive than this code when the rules are necessary to protect life or property in the 17 18 community. The governing body may adopt this code by ordinance. One certified copy of the ordinance containing the 19 20 rules shall be filed with the clerk of the jurisdiction and shall be in effect immediately thereafter, and additional copies 21 shall be kept in the office of the fire department for 22 distribution to the public. 23

(c) Chief Defined. Wherever the term "chief" appears in
Articles 2 to 87 or in the Appendix of this code, it shall mean
state fire marshal, except that it shall also include the chief
of any jurisdiction adopting this code.

Subp. 2. Sec. 2.103. Sec. 2.103 of the Uniform Fire Code is amended to read:

Sec. 2.103. A fire prevention bureau may be established within the fire department under the direction of the fire chief, which shall consist of such fire department personnel as may be assigned thereto by the fire chief. The function of this bureau shall be to assist the fire chief in the administration and enforcement of the fire prevention provisions of this code. Subp. 3. Sec. 2.202. Sec. 2.202 of the Uniform Fire Code

2

08/21/89

1 is amended to read:

2 Sec. 2.202. (a) Investigation. The fire department of any 3 jurisdiction adopting this code shall investigate promptly the cause, origin, and circumstances of each and every fire 4 5 occurring in the municipality involving loss of life or injury to person or destruction or damage to property, and if it 6 7 appears to the members of the fire department making the 8 investigation that such fire is of suspicious origin, they shall 9 then take immediate charge of all physical evidence relating to 10 the cause of fire, shall notify the proper authorities designated by law to pursue the investigation of such matters, 11 12 and shall cooperate with the authorities in the collection of 13 evidence and in the prosecution of the case. The chief shall make a report in writing to the state fire marshal of all facts 14 and findings relative to each investigation. 15

16 (b) Police Department Assistance. The police department 17 may assist the fire department in its investigation whenever 18 requested to do so.

19 Subp. 4. Sec. 2.205. Sec. 2.205 of the Uniform Fire Code 20 is amended to read:

21 Sec. 2.205. Any order or notice authorized or required by 22 this code shall be given or served upon the owner, operator, occupant, or other person responsible for the condition or 23 24 violation either by oral notification, personal service, or by delivering the same to and leaving it with some person of 25 suitable age and discretion upon the premises; or, if no such 26 person is found on the premises, by affixing a copy thereof in a 27 conspicuous place on the door to the entrance of said premises 28 and by mailing a copy thereof to such person by mail to the 29 person's last known address. Orders or notices given orally 30 31 shall be confirmed by service in writing as herein provided.

32 Subp. 5. Sec. 2.303. Sec. 2.303 of the Uniform Fire Code 33 is deleted.

Subp. 6. Sec. 2.304(b). The first paragraph of Sec. 35 2.304(b) of the Uniform Fire Code is deleted and replaced with 36 the following:

> Approved by Revisor

08/21/89

Sec. 2.304. (b) Recognized Standards. The following
 standards are intended for use as a guide in the design,
 fabrication, testing, and use of equipment regulated by this
 code:

5 Subp. 7. Sec. 2.304(c). Sec. 2.304 of the Uniform Fire 6 Code is amended by adding a subsection to read:

7 Sec. 2.304. (c) Standard 101 Incorporated. Whenever the Uniform Fire Code, as amended by parts 7510.3100 to 75±0-3270 8 9 7510.3280, is silent on any subject, for any reason, in any situation, the provision of protection shall be in accordance 10 with National Fire Codes, 1988, Standard Number 101, issued by 11 12 the National Fire Protection Association (Quincy, Massachusetts, 1988) which is adopted by reference as part of this code as 13 14 though set forth herein in its entirety. Standard Number 101 is 15 not subject to frequent change and is available at the State Law Library, 117 University Avenue, Saint Paul, Minnesota 55155. 16

17 7510.3150 ARTICLE 4 OF UNIFORM FIRE CODE.

Subpart 1. Sec. 4.103. Sec. 4.103 of the Uniform Fire
Code is amended to read:

Sec. 4.103. All applications for a permit required by this code shall be made to the chief in such form and detail as required by the chief. Applications for permits shall be accompanied by such plans as required by the chief.

24 Subp. 2. Sec. 4.108. The first sentence of Sec. 4.108 of 25 the Uniform Fire Code is amended to read:

Sec. 4.108. When required by the chief, a permit shall be obtained prior to engaging in the following activities, operations, practices, or functions:

29 7510.3160 ARTICLE 9 OF UNIFORM FIRE CODE.

30 Subpart 1. Sec. 9.103; adult day-care center defined. Sec.
31 9.103 of the Uniform Fire Code is amended by adding a definition
32 to read:

33 Sec. 9.103. ADULT DAY-CARE CENTER shall mean a facility, 34 licensed by the Department of Human Services under Minnesota 35 Rules, parts 9555.9600 to 9555.9730, which provides a program of

4

08/21/89

services to adults for periods of less than 24 hours per day.
 Subp. 2. Sec. 9.103; authority having jurisdiction
 defined. Sec. 9.103 of the Uniform Fire Code is amended by
 adding a definition to read:

5 Sec. 9.103. AUTHORITY HAVING JURISDICTION shall mean any 6 municipal fire code official or the state fire marshal or any of 7 their authorized representatives.

8 Subp. 3. Sec. 9.104; Building Code definition amended. 9 The definition of Building Code in Sec. 9.104 of the Uniform 10 Fire Code is amended to read:

Sec. 9.104. BUILDING CODE shall mean the Minnesota State
Building Code.

Subp. 4. Sec. 9.108; family day-care home defined. Sec.
9.108 of the Uniform Fire Code is amended by adding a definition
to read:

Sec. 9.108. FAMILY DAY-CARE HOME shall mean a residence, licensed by the Department of Human Services under Minnesota Rules, parts 9502.0315 to 9502.0445, in which no more than ten children receive care, maintenance, and supervision by other than their relatives or legal guardians for less than 24 hours per day.

Subp. 5. Sec. 9.109; group day-care home defined. Sec. 9.109 of the Uniform Fire Code is amended by adding a definition to read:

25 Sec. 9.109. GROUP DAY-CARE HOME shall mean a residence, 26 licensed by the Department of Human Services under Minnesota 27 Rules, parts 9502.0315 tc 9502.0445, in which at least 11 but 28 not more than 14 children receive care, maintenance, and 29 supervision by other than their relatives or legal guardians for 30 less than 24 hours per day.

Subp. 6. Sec. 9.109; guest room defined. Sec. 9.109 of the Uniform Fire Code is amended by adding a definition to read: Sec. 9.109. GUEST ROOM shall mean a room used exclusively for living or sleeping purposes excluding storage rooms, laundry rooms, furnace rooms, and similar common areas. Every 100 square feet of superficial floor area in a dormitory shall be

5

08/21/89

1 considered to be a guest room.

Subp. 7. Sec. 9.115; mechanical code definition amended.
The definition of mechanical code in Sec. 9.115 of the Uniform
Fire Code is amended to read:

5 Sec. 9.115. MECHANICAL CODE shall mean the Minnesota
6 Heating, Ventilation, Air Conditioning and Refrigeration Code,
7 in Minnesota Rules, chapter 1345.

8 Subp. 8. Sec. 9.115; municipality defined. Sec. 9.115 of 9 the Uniform Fire Code is amended by adding a definition to read: 10 Sec. 9.115. MUNICIPALITY shall mean any statutory or home 11 rule charter city, county, or town meeting the requirements of 12 Minnesota Statutes, section 368.01, subdivision 1, the 13 University of Minnesota, or the state for public buildings.

Subp. 9. Sec. 9.117; Group E Occupancies definition
amended. The definition of Group E Occupancies in Sec. 9.117 of
the Uniform Fire Code is amended to read:

17

Sec. 9.117. Group E Occupancies:

Division 1. Any building used for educational purposes through the 12th grade by 50 or more persons for more than 12 hours per week or four hours in any one day.

Division 2. Any building used for educational purposes through the 12th grade by less than 50 persons for more than 12 hours per week or four hours in any one day.

Division 3. Any building used for child day-care purposes for more than ten children, or for adult day-care centers serving four or more ambulatory and mobile persons who are capable of taking appropriate action for self-preservation under emergency conditions as determined by program licensure provisions.

30 Subp. 10. Sec. 9.117; Group I Occupancies definition
31 amended. The definition of Group I Occupancies in Sec. 9.117 of
32 the Uniform Fire Code is amended to read:

33

Sec. 9.117. Group I Occupancies:

Division 1. Nurseries for the full-time care of children under the age of six, each accommodating more than four persons; and, hospitals, sanitariums, nursing homes, and similar

6

08/21/89

36

1 buildings, each accommodating more than four persons. 2 Division 2. Detoxification centers; homes for children six years of age or over; Class B supervised living facilities for 3 the mentally retarded, mentally ill, or the physically 4 5 handicapped, defined in Sec. 9.121; and, adult day-care centers serving ambulatory, nonambulatory, mobile, or nonmobile persons 6 7 who are not mentally or physically capable of taking appropriate action for self-preservation under emergency conditions as 8 determined by program licensure provisions, each accommodating 9 more than four persons. 10 11 EXCEPTION: Adult day-care centers meeting the 12 following criteria may be classified as Group E, 13 Division 3 Occupancies: 14 1. not more than 50 percent of the center's licensed 15 capacity shall be made up of participants who are not 16 capable of taking appropriate action for 17 self-preservation under emergency conditions; 18 2. the center shall be located on a floor level with 19 all exits directly to grade without intervening 20 stairs; 21 3. the center shall be protected with a complete 22 automatic fire detection system consisting of: 23 (i) automatic smoke detectors in all corridors and at 24 the top of all stairways; 25 (ii) automatic detectors in boiler and furnace rooms, 26 kitchens, storage rooms, janitor closets, laundries, and 27 other hazardous areas; and 28 (iii) in buildings equipped with manual fire alarm 29 systems, the manual fire alarm and automatic detection 30 systems shall be electrically interconnected; and 31 the center shall demonstrate the ability to 4. 32 evacuate the entire center population within three 33 minutes. 34 Division 3. Mental hospitals, mental sanitariums, jails, 35 prisons, reformatories, and buildings where personal liberties

> Approved by Revisor _

7

of inmates are similarly restrained.

35

36

to read:

[REVISOR] RR/MM AR1431

1 EXCEPTION: Group I Occupancies shall not include 2 buildings used only for private residential purposes 3 or for a family group. 4 Subp. 11. Sec. 9.117; Group R Occupancies definition amended. The definition of Group R Occupancies in Sec. 9.117 of 5 the Uniform Fire Code is amended to read: 6 7 Sec. 9.117. Group R Occupancies: 8 Division 1. Hotels and apartment houses. Convents and 9 monasteries, each accommodating more than ten persons; and Class A-2 supervised living facilities, defined in Sec. 9.121, for the 10 mentally retarded, mentally ill, chemically dependent, and 11 physically handicapped, each accommodating more than four 12 13 persons. Physically handicapped persons shall be housed at street level in supervised living facilities. 14 15 EXCEPTION: Class A-2 supervised living facilities, 16 defined in Sec. 9.121, having more than six but not 17 more than 15 ambulatory or mobile disabled persons, 18 duly licensed before April 11, 1983, and complying 19 with the requirements for lodging and rooming houses 20 as set forth in Standard 101 in the National Fire 21 Codes, 1973, issued by the National Fire Protection 22 Association (Boston, Massachusetts, 1973), are classified as Group R, Division 3 Occupancies. 23 24 Division 2. Not used. 25 Division 3. Dwellings, lodging houses, and Class A-1 26 supervised living facilities defined in Sec. 9.121. 27 Subp. 12. Sec. 9.120; required by chief defined. Sec. 9.120 of the Uniform Fire Code is amended by adding a definition 28 29 to read: 30 Sec. 9.120. REQUIRED BY THE CHIEF shall mean determined by the chief to be directly related to the safeguarding of life and 31 32 property from the hazards of fire and uniform for each class or 33 kind of building, structure, or property covered. 34 Subp. 13. Sec. 9.121; state fire marshal defined. Sec.

> Approved by Revisor

8

9.121 of the Uniform Fire Code is amended by adding a definition

08/21/89

Sec. 9.121. STATE FIRE MARSHAL shall mean the Minnesota
 state fire marshal or the state fire marshal's authorized
 representatives.

Subp. 14. Sec. 9.121; supervised living facility defined.
Sec. 9.121 of the Uniform Fire Code is amended by adding a
definition to read:

7 Sec. 9.121. SUPERVISED LIVING FACILITY means a facility in 8 which supervision, lodging, meals, and in accordance with the 9 rules of the Department of Human Services and the Department of 10 Health, counseling and developmental habilitative or 11 rehabilitative services are provided to five or more persons who 12 are mentally retarded, chemically dependent, adult mentally ill, 13 or physically handicapped.

14 Class A supervised living facility shall mean a supervised 15 living facility for ambulatory and mobile persons who are 16 capable of taking appropriate action for self-preservation under 17 emergency conditions as determined by program licensure 18 provisions.

19 Class A-1 supervised living facilities shall include homes 20 providing boarding and lodging for six or fewer ambulatory or 21 mobile disabled persons.

Class A-2 supervised living facilities shall include homes providing boarding and lodging for more than six ambulatory or mobile disabled persons.

Class B supervised living facility shall mean a supervised living facility for ambulatory or nonambulatory, mobile or nonmobile persons who are not mentally or physically capable of taking appropriate action for self-preservation under emergency conditions as determined by program licensure provisions.

30 7510.3170 ARTICLE 10 OF UNIFORM FIRE CODE.

31 Subpart 1. Sec. 10.207(m). Sec. 10.207 of the Uniform 32 Fire Code is amended by adding a subsection to read:

33 Sec. 10.207. (m) Marking Fire Lanes. The marking of fire 34 lanes on private and public property shall be designated and 35 approved by the chief.

9

1	Subp. 2. Sec. 10.207(n). Sec. 10.207 of the Uniform Fire
2	Code is amended by adding a subsection to read:
3	Sec. 10.207. (n) Obstruction of Fire Lanes. Parking of
4	motor vehicles in, or otherwise obstructing, fire lanes shall be
5	prohibited at all times.
6	Subp. 3. Sec. 10.301(f). Sec. 10.301(f) of the Uniform
7	Fire Code is amended to read:
8	Sec. 10.301. (f) Approval and Testing. All fire alarm
9	systems, fire hydrant systems, fire-extinguishing systems
10	(including automatic sprinklers), wet and dry standpipes,
11	basement inlet pipes, and other fire-protection systems and
12	appurtenances thereto shall meet the approval of the chief as to
13	installation and location and shall be subject to periodic tests
14	required by the chief. Plans and specifications shall be
15	submitted to the chief for review and approval before
16	installation.
17	Subp. 4. Sec. 10.309(b). Sec. 10.309(b) of the Uniform
18	Fire Code is amended to read:
19	Sec. 10.309. (b) Where Required. Standpipe systems shall
20	be provided as set forth in Table No. 10.309 and shall have a
21	constant water supply and pressure.
22	EXCEPTION: Dry standpipes may be installed with prior
23	approval of the chief.
24	Subp. 5. Table No. 10.309. Table No. 10.309, Item No. 2,
25	"Occupancy" column, of the Uniform Fire Code is amended to read:
26	TABLE NO. 10.309. Item No. 2, "Occupancy" column:
27	Occupancies 3 stories or more but less than 150 feet in height,
28	except Group R, Division 3. Class II standpipes are not
29	required in Group E or Group R-1 Occupancies.
30	7510.3180 ARTICLE 11 OF UNIFORM FIRE CODE.
31	Subpart 1. Sec. 11.117. Article 11 of the Uniform Fire
32	Code is amended by adding a section to read:
33	Fires or Barbecues on Balconies or Patios
34	Sec. 11.117. (a) Open Flame Prohibited. When required by
35	the chief, in any structure containing three or more dwelling
	가지 않는 것 같은 것 같

08/21/89

Approved by Revisor

08/21/89

units, no person shall kindle, maintain, or cause any fire or
 open flame on any balcony above ground level, or on any ground
 floor patio within 15 feet of the structure.

(b) Fuel Storage Prohibited. No person shall store or use 4 any fuel, barbecue, torch, or other similar heating or lighting 5 6 chemical or device in the locations designated in subsection (a). 7 **EXCEPTION:** Listed electric or gas-fired barbecue 8 grills that are permanently mounted, wired, or plumbed 9 to the building's gas supply or electrical system and 10 that maintain a minimum clearance of 18 inches on all 11 sides, unless listed for lesser clearances, may be installed on balconies and patios when approved by the 12 13 chief.

Subp. 2. Sec. 11.204. Sec. 11.204 of the Uniform Fire
Code is amended by adding an Exception to read:

16 Sec. 11.204. Exception. For requirements relating to 17 Christmas trees, see Sec. 11.210.

Subp. 3. Sec. 11.210. Article 11 of the Uniform Fire Code is amended by adding a section to read:

20 Christmas Trees

Sec. 11.210. (a) Group I Occupancies. The use or display of natural or resin-bearing trees or decorations in Group I Occupancies is prohibited.

(b) Public Buildings. The use, display, or storage of
natural or resin-bearing trees without open flames or electric
light decorations is permitted in schools, churches, hotels, and
business and mercantile occupancies. See Sec. 11.203(c).

(c) Flame-retardant Artificial Trees. The use or display
of flame-retardant artificial trees decorated with U.L. listed
electric lighting systems is acceptable in all occupancies.

31 (d) R-1 Occupancies. Natural or resin-bearing trees shall 32 not be stored on balconies or grounds of R-1 Occupancies. See 33 Sec. 11.203(c).

34 Subp. 4. Sec. 11.302(e). Sec. 11.302 of the Uniform Fire
35 Code is amended by adding a subsection to read:
36 Sec. 11.302. (e) Misdemeanor. Whoever intentionally gives

Approved by Revisor _

08/21/89

1 a false alarm of fire, or unlawfully tampers or interferes with 2 any station or signal box of any fire alarm system or any 3 auxiliary fire appliance, or unlawfully breaks, injures, 4 defaces, or removes any such box or station, or unlawfully 5 breaks, injures, destroys, or disturbs any of the wires, poles, 6 or other supports and appliances connected with or forming a 7 part of any fire alarm system or any auxiliary fire appliance is 8 guilty of a misdemeanor.

9 7510.3190 ARTICLE 12 OF UNIFORM FIRE CODE.

Subpart 1. Sec. 12.101. Sec. 12.101 of the Uniform Fire
Code is amended by adding a paragraph to read:

Sec. 12.101. Egress requirements in family and group day-care homes located in a single family dwelling located on a residential lot in which the day-care provider provides the services referred to in Minnesota Statutes, section 245A.02, subdivision 10, to one or more persons, shall not exceed the egress requirements that apply to the home as a single family dwelling.

Subp. 2. Sec. 12.106(a). Sec. 12.106(a) of the Uniform
Fire Code is amended to read:

Sec. 12.106. (a) General. Stairways shall conform to the provisions of the Building Code.

EXCEPTION: Stairs or ladders used only to attend equipment are exempt from the requirements of this section when properly maintained.

26 7510.3200 ARTICLE 14 OF UNIFORM FIRE CODE.

27 Sec. 14.104(b). Sec. 14.104(b) of the Uniform Fire Code is 28 amended to read:

29 Sec. 14.104. (b) Type of System. A manual or 30 automatic fire alarm system or both shall be installed in 31 occupancies in accordance with the following:

32 1. A manual fire alarm system shall be installed 33 in:

12

A. Group A, Divisions 1, 2, and 2.1

35 Occupancies

08/21/89 [REVISOR] RR/MM AR1431 1 в. Group H Occupancies used for the 2 manufacture of organic coatings 3 C. Group H, Division 6 Occupancies as set forth in Article 51 4 5 2. An automatic fire alarm system shall be 6 installed in: 7 Group B, Division 2 Occupancies as set Α. 8 forth in Chapter 33 of the Building Code 9 в. As set forth in Article 81 of this code 10 A manual and automatic fire alarm system 3. shall be installed in: 11 12 Α. Group E Occupancies having more than 50 occupants and as set forth in Chapter 33 of the Building Code, 13 14 and in Group E, Division 3 Occupancies having more than 29 15 occupants. In every Group E Occupancy with an automatic sprinkler or detection system, the operation of the system must 16 automatically activate the building fire alarm system. 17 18 In Group E Occupancies, an approved fire alarm system shall 19 mean a complete, noncoded, continuously sounding until manually reset, electronically supervised fire alarm system consisting of 20 the following: 21 22 (i) Sounding stations on 100-foot to 150-foot spacing: (1) in corridors, (2) in areas of high noise 23 24 levels, such as band rooms, shops, and boiler rooms, and (3) on 25 a weatherproof station on the exterior of the building facing 26 residential areas. 27 (ii) Automatic sending stations (detectors) in boiler rooms, kitchens, shops, painting areas, 28 lounges, laundries, janitor's closets, storerooms, unsupervised 29 and unoccupied spaces, and critical or hazardous areas. 30 31 (iii) Unobstructed, readily accessible manual sending stations at visible locations in the natural path 32 33 of escape from fire, near each exit from an area on each floor. 34 B. Group I Occupancies 35 С. Group R, Division 1 Occupancies 36 specified in subsection (c).

13

Approved

by Revisor

1 7510.3210 ARTICLE 26 OF UNIFORM FIRE CODE. 2 Subpart 1. Title. The title of Article 26 of the Uniform Fire Code is deleted and replaced with the following: 3 4 RESURFACING AND REFINISHING Sec. 26.101. Sec. 26.101 of the Uniform Fire 5 Subp. 2. Code is amended to read: 6 7 Sec. 26.101. Bowling alleys, roller skating rinks, and other public assembly occupancies shall conform to all other 8 applicable requirements of this code, as well as the following 9 10 provisions. Subp. 3. Sec. 26.102. Sec. 26.102 of the Uniform Fire 11 12 Code is amended to read: Sec. 26.102. No person shall conduct bowling pin 13 14 refinishing and bowling alley or floor resurfacing and 15 refinishing operations involving the use and application of flammable liquids or materials without a local permit. 16 17 Subp. 4. Sec. 26.103. The subtitle of Sec. 26.103 of the Uniform Fire Code is amended to read: 18 Resurfacing and Refinishing 19 20 Subp. 5. Sec. 26.104. The subtitle of Sec. 26.104 of the Uniform Fire Code is amended to read: 21 22 Refinishing 23 7510.3220 ARTICLE 61 OF UNIFORM FIRE CODE. Sec. 61.105 of the Uniform Fire Code is amended to read: 24 25 Sec. 61.105. The grade of fuel oil used in a burner shall 26 be that for which the burner is approved and as stipulated by the manufacturer. The installation and use of waste oil burners 27 shall conform to the provisions of Minnesota Statutes, section 28 299F.015. 29 7510.3230 ARTICLE 77 OF UNIFORM FIRE CODE. 30 31 Subpart 1. Sec. 77.104. Sec. 77.104 of the Uniform Fire 32 Code is deleted. Subp. 2. Sec. 77.105. Sec. 77.105 of the Uniform Fire 33

08/21/89

34

Code is deleted.

Approved by Revisor

35

7510.3240 ARTICLE 79 OF UNIFORM FIRE CODE. 1 2 Subpart 1. Sec. 79.101(a). Sec. 79.101(a), Exception 1 of 3 the Uniform Fire Code is amended to read: Sec. 79.101. (a) General. 4 **EXCEPTIONS:** 5 1. The transportation of flammable and combustible 6 7 liquids when in conformity with the United States Department of Transportation regulations on file with 8 9 and approved by the United States Department of 10 Transportation. 11 Subp. 2. Sec. 79.101(d). Sec. 79.101 of the Uniform Fire Code is amended by adding a subsection to read: 12 Sec. 79.101. (d) Review of Plans. Requirements for the 13 review of plans, as covered in the following items 1 to 7, are 14 15 herein incorporated as part of this code, to read: 16 1. Before any construction or new or additional 17 installation for the storage, handling, or use of flammable 18 liquids is undertaken in bulk plants, service stations, chemical 19 plants, refineries, and processing plants, drawings or 20 blueprints of them made to scale shall be submitted to the state 21 fire marshal with an application, all in duplicate, for review. 22 Within a reasonable time, usually ten days after receipt of the 23 application with drawings or blueprints, the state fire marshal shall examine them. On finding that they conform to the 24 25 applicable requirements of this code, the state fire marshal 26 shall so signify either by endorsement on them or by attachment 27 to them, retain one file copy, and return to the applicant the 28 other copy plus any additional copies submitted by the applicant. If the drawings or blueprints do not conform to the 29 30 applicable requirements of this code, the state fire marshal 31 shall notify the applicant in writing within the time allowed 32 for the examination of the application. 33 2. Drawings shall show the name of the person, 34 firm, or corporation proposing the installation, its location,

> Approved by Revisor _

15

and the adjacent streets or highways and surface waters of the

08/21/89

state.

1

2 3. In the case of bulk plants, the drawings shall show, in addition to any applicable features required 3 under items 5 and 6, the plot of ground to be utilized and its 4 immediate surroundings on all sides; complete layout of 5 buildings, tanks, and loading and unloading docks; type of 6 7 construction of each building and the type and location of heating devices for each building, if any. 8 9 4. In the case of service stations, the drawings, in addition to any applicable features required under 10 11 items 5 and 6, shall show the plot of ground to be utilized; the complete layout of buildings, drives, dispensing equipment, and 12 greasing or washing stalls; and the type and location of any 13 heating devices. 14 15 5. In the case of aboveground storage, the 16 drawings shall show the location and capacity of each tank; dimensions of each tank that has a capacity exceeding 50,000 17 gallons; the class of liquids to be stored in each tank; the 18 19 type of tank supports; the clearance as covered in sections 79.503 and 79.504; the type of venting and pressure relief 20 relied upon and the combined capacity of all venting and 21 22 pressure relief valves on each tank, as covered in Sec. 79.509; the tank control valves as covered in Sec. 79.509(c); the 23 location of the pumps and other facilities by which liquid is 24 filled into and withdrawn from the tanks; and diking provided, 25 26 if any. 6. In the case of underground storage, the 27 drawings shall show the locations of fill gauge and vent pipes 28 and openings, the location and capacity of each tank, and the 29 class of liquid to be stored in each tank, along with the 30 clearance and requirements as covered in sections 79.601 to 31 79.605. 32

33 7. In the case of an installation for storage,
34 handling, or use of flammable liquids within buildings or
35 enclosures at any establishment or occupancy covered in this
36 section, the drawings shall be in such detail as will show

Approved by Revisor

whether applicable requirements are to be met. 1 2 Subp. 3. Sec. 79.902(e). Sec. 79.902(e) of the Uniform 3 Fire Code is amended by adding an exception to read: Sec. 79.902. (e) Dispensing. 4 5 EXCEPTION: When approved by the chief, the dispensing 6 of Class I and Class II liquids from a fuel dispensing 7 system supplied by exterior aboveground tanks may be 8 permitted under the following conditions: 9 Not more than three aboveground storage tanks 1. 10 shall be used for dispensing. Tanks shall not exceed 11 6,000 gallons individual capacity. 12 2. The tank system shall be listed or approved for 13 such aboveground use. 14 3. Fuel delivery from aboveground tanks shall be from 15 the top of the tank with the dispensing line equipped 16 with an approved antisyphon system, or by a remote 17 submersible pump system located in a tank of not over 60 gallons capacity attached to the main storage tank, 18 19 provided the line between the main tank and the remote pump is equipped with a normally closed solenoid valve 20 21 and fire valve at the tank opening. 4. Dispensing lines between the diked area and the 22 23 dispenser shall be located underground. These lines 24 shall be equipped with approved leak detection devices 25 connected to an audible and visual alarm as required 26 by the chief. These lines shall also be equipped with 27 approved excess flow valves and a normally closed 28 solenoid valve at each dispenser located below the 29 impact valve. 30 The tank shall be equipped with overfill 5. 31 protection and the fill pipe between the opening and the diked area shall be underground. In addition to 32 the normal valving requirements of the code, there 33 34 shall be a manually operated, mechanical shut-off 35 valve on the fill line inside the diked area which is operated from a location outside the dike. 36

17

1 6. Dispensing lines and fill piping shall not 2 penetrate the dike. 3 7. The tanks and piping shall be safeguarded against 4 collision, spillage, and overfill as required by the 5 chief. 6 8. The tanks shall comply with requirements for 7 emergency relief venting, and the tanks and dispensing 8 system shall meet the electrical classification 9 requirements of the code. 10 9. Tanks, piping, valves and fittings, and diking shall be constructed and maintained in accordance with 11 Article 79. 12 13 10. Tanks shall be provided with lightning protection 14 as specified in National Fire Protection Association 15 Standard 78, Lightning Protection Code, by the 16 National Fire Protection Association (Quincy, Massachusetts, 1986). Standard 78 is incorporated by 17 18 reference, is not subject to frequent change, and is 19 available at the State Law Library, 117 University 20 Avenue, Saint Paul, Minnesota 55155. 21 11. Tank location and distance shall be two times 22 that specified in sections 79.503 and 79.504, but not 23 less than 30 feet from the nearest side of any public 24 way or from the nearest building and dispensing units 25 on the same property. 26 12. Where more than one tank is used, all aboveground 27 tanks shall be protected by an approved fire 28 protection system when required by the chief. 29 13. Variances shall not be granted from any of the 30 provisions contained in items 2 to 12. 31 Subp. 4. Sec. 79.903(a). The first paragraph of Sec. 32 79.903(a) of the Uniform Fire Code is amended to read: 33 Sec. 79.903. (a) Design and Construction. Except as otherwise provided in Sec. 79.902(e), Class I and Class II 34 35 liquids shall be transferred from underground tanks by means of 36 fixed pumps so designed and equipped as to allow control of the

18

Approved

by Revisor

08/21/89

flow and to prevent leakage or accidental discharge. 1 Supplemental means shall be provided outside of the dispensing 2 device so that the source of power may be readily disconnected 3 4 in the event of fire or other accident. Dispensing devices for Class I, II, or III-A liquids shall be of approved type. 5 See Sec. 2.303(b). Class I, II, or III-A liquids shall be dispensed 6 7 by approved pumps taking suction through the top of the container. Class I, II, or III-A liquids shall not be dispensed 8 by a device that operates through pressure within a storage tank 9 or container unless the tank or container has been approved as a 10 11 pressure vessel for the use to which it is subjected. In no case shall air or oxygen pressure be used for dispensing 12 flammable Class I, II, or III-A liquids. This section does not 13 prohibit use permitted by Sec. 79.904. 14

Subp. 5. Sec. 79.903(g). Sec. 79.903 of the Uniform Fire
Code is amended by adding a subsection to read:

Sec. 79.903. (g) Age Requirement. Flammable and combustible liquids shall be dispensed only by persons 16 years of age or older. Prominent signs shall be posted at self-service stations prohibiting flammable liquids from being dispensed by anyone under age 16.

22 7510.3250 ARTICLE 80 OF UNIFORM FIRE CODE.

23 Sec. 80.104(e) of the Uniform Fire Code is amended to read: 24 Sec. 80.104. (e) IDENTIFICATION. Visible hazard identification signs as specified in Uniform Fire Code 25 Standards, Standard No. 79-3, Identification of the Health, 26 Flammability, and Reactivity of Hazardous Materials, published 27 by the International Conference of Building Officials and the 28 29 Western Fire Chiefs Association, 1988, (Whittier, California), shall be placed at entrances to locations where hazardous 30 31 materials are stored, dispensed, used, or handled in quantities requiring a permit. The chief shall designate the specific 32 entrances where signs are required. 33

34 The chief may waive this requirement in special cases when 35 consistent with safety, if the facility owner or operator, in

19

08/21/89

1

38

39

08

09

conjunction with the chief, develops an approved preemergency plan consistent with the Hazardous Materials Management Plan 2 3 (HMMP) in Appendix II-E. The owner or operator shall make copies of this plan available to other emergency response 4 5 agencies on request. 6 In addition, when required by the chief, hazard 7 identification signs mounted on a building shall include a sign 8 indicating the hazard type and range value for the average daily amount of hazardous materials present, as required on the Tier 1 9 10 hazardous chemical inventory form under the Superfund Amendments 11 and Reauthorization Act of 1986, Public Law Number 99-499, 12 section 312, subsection (d)(1) "Tier I Information," which is 13 incorporated by reference. The placard symbols for hazard type 14 and range value are as follows: 15 1. HAZARD TYPE: 16 Physical Hazards 17 Fire - The 3-letter placard abbreviation is: FIR Sudden Release of Pressure - The 3-letter placard 18 19 abbreviation is: SRP 20 Reactivity - The 3-letter placard abbreviation is: REA 21 Health Hazards 22 Immediate (acute) - The 3-letter placard abbreviation is: 23 HHI 24 Delayed (chronic) - The 3-letter placard 25 abbreviation is: HHD 26 2. RANGE VALUE: 27 Weight Range in Pounds 28 Placard Abbreviation From To 29 None Present 30 00 0 99 31 01 100 999 32 02 1,000 9,999 33 03 10,000 99,999 34 04 100,000 999,999 35 05 1,000,000 9,999,999 36 06 10,000,000 49,999,999 37 07 50,000,000 99,999,999

Approved

by Revisor _

499,999,999

999,999,999

20

100,000,000

500,000,000

1

10

1 billion or greater

2 7510.3260 ARTICLE 82 OF UNIFORM FIRE CODE.

3 Sec--82:102-of-the-Uniform-Fire-Code-is-amended-by-adding-a
4 subsection-to-read:

5 Subpart 1. Article 82. Article 82 of the Uniform Fire 6 Code is deleted in its entirety and replaced with the following: 7 Sec. 82.101. LP Gas Storage and Handling. The storage, handling, transportation, and use of liquified petroleum gas and 8 the installation of all equipment pertinent to systems for such 9 uses shall be designed, constructed, installed, operated, and 10 maintained in accordance with the provisions of U.F.C. Standard 11 12 No. 82-1.

13 <u>Sec. 82.102.</u> LP Gas Systems at Utility Gas Plants. <u>The</u> 14 <u>design, construction, location, installation, and operation of</u> 15 <u>refrigerated and nonrefrigerated liquified petroleum gas systems</u> 16 <u>at utility gas plants shall be in accordance with the provisions</u> 17 <u>of U.F.C. Standard No. 82-2.</u>

18 Sec.-82:102:--(d) Sec. 82.103. Submittal of Plans. Where 19 an underground container is permitted, plans of its 20 installation, regardless of capacity, shall be submitted for 21 review to the state fire marshal before construction.

For any installation utilizing aboveground storage containers of over 2,000 gallons water capacity, or when aggregate water capacity of all aboveground containers exceeds 4,000 gallons, plans shall be submitted to the state fire marshal before construction.

27 <u>Subp. 2.</u> Uniform Fire Code Standard No. 82-1. Part I of
 28 <u>Uniform Fire Code Standard No. 82-1 is deleted in its entirety.</u>

29 7510.3270 ARTICLE 85 OF UNIFORM FIRE CODE.

Sec. 85.109 of the Uniform Fire Code is amended to read:
 Sec. 85.109. Electrical appliances or fixtures shall not
 be used unless they are of an approved type.

33 7510.3280 AMENDMENTS TO APPENDIXES OF UNIFORM FIRE CODE.

34 Subpart 1. Adoption. Appendixes I-A, I-C, II-A, II-B,

21

Approved

by Revisor

08/21/89

II-C, IV-A, and VI-D of the Uniform Fire Code, as amended by 1 2 this part, shall be deemed a part of this code and shall be enforced as such. 3

Subp. 2. Appendix I-A, Sec. 1(b). Appendix I-A, Sec. 4 5 1(b), is deleted in its entirety.

6 Subp. 3. Appendix I-A, Sec. 2(a). The first paragraph and 7 the accompanying exception in Appendix I-A, Sec. 2(a), are amended to read: 8

9

Sec. 2. EXITS

10 (a) Number of Exits. Every basement and every floor above 11 the first story used for human occupancy shall have access to at 12 least two separate exits, one of which may be an exterior fire escape complying with subsection (d) of this section. Subject 13 to the approval of the chief, an approved ladder device may be 14 15 used in lieu of a fire escape when the construction feature or location of the building on the property makes the installation 16 of a fire escape impractical. 17

18 **EXCEPTIONS:**

1. In all occupancies, basements and second stories 19 20 with an occupant load of ten or less may have one exit. 21 2. When the third floor within an individual dwelling unit does not exceed 500 square feet, only one exit 22 23 need be provided from that floor.

24 Floors and basements used exclusively for service 3. of the building may have one exit. For the purposes 25 of this exception, storage rooms, laundry rooms, 26 maintenance offices, and similar uses shall not be 27 28 considered as providing service to the building. 4. Storage rooms, laundry rooms, and maintenance 29 offices not exceeding 300 square feet in floor area 30 31 may be provided with only one exit.

Subp. 4. Appendix I-A, Sec. 2(c). Appendix I-A, Sec. 32 2(c), is amended to read: 33

Sec. 2. EXITS 34

35 (c) Corridors. Corridors serving a Group R, Division 1 or Group I Occupancy having an occupant load of ten or more and 36

22

[REVISOR] RR/MM AR1431

1 corridors serving other occupancies having an occupant load of 2 30 or more shall have walls and ceilings of not less than one-hour fire-resistive construction as required by the Building 3 Code. Existing walls surfaced with wood lath and plaster in 4 good condition or 1/2-inch gypsum wallboard or openings with 5 fixed wired glass set in steel frames are permitted for corridor 6 walls and ceilings and occupancy separations when approved. 7 8 Doors opening into such corridors shall be protected by 20-minute fire assemblies or solid wood doors not less than 9 1-3/4 inches thick. Where the existing frame will not 10 11 accommodate the 1-3/4 inches thick door, a 1-3/8 inches thick solid bonded wood core door or equivalent insulated steel door 12 shall be permitted. Doors shall be self-closing or 13 automatic-closing by smoke detection. Transoms and openings 14 15 other than doors from corridors to rooms shall comply with 16 Section 3305(h) of the Building Code or shall be covered with a 17 minimum of 3/4-inch plywood or 1/2-inch gypsum wallboard or equivalent material on the room side. 18 19 EXCEPTION: Existing corridor walls, ceilings, and 20 opening protection not in compliance with the above 21 may be continued when such buildings are protected 22 with an approved automatic sprinkler system throughout. Such sprinkler system may be supplied 23 24 from the domestic water system if it is of adequate volume and pressure. 25 26 Subp. 5. Appendix I-A, Sec. 5. Appendix I-A, Sec. 5, is amended to read: 27 Sec. 5. STANDPIPES 28 When required by the chief, any building three stories or 29 more in height shall be provided with an approved Class I or 30 Class III standpipe system. 31 32 33 REPEALER. Minnesota Rules, parts 7510.0200, 7510.0300, 7510.0400, 7510.0500, 7510.1100, 7510.1200, 7510.1300, 34 7510.1400, 7510.1500, 7510.1600, 7510.1700, 7510.1800, 35 7510.1900, 7510.2000, 7510.2100, 7510.2200, 7510.2300, 36

> Approved by Revisor _

7510.2400, 7510.2500, 7510.3000, 7510.4100, 7510.4200,
 7510.4300, 7510.4400, 7510.5100, 7510.5200, 7510.5300, and
 7510.5400, are repealed.

STATE OF MUNICOTA DEPARTMENT OF STATE RES